

TITAN 2200/3200

**Right- and lefthand fringing machines.
Fringes both sides of the carpet simultaneously.
Reduces costs & doubles the production.**

APPLICATIONS

Produces complete decorative fringe starting from one thread on carpets, shawls and house linen.
Left and righthand models available to be included in fully automatic lines.



ALWAYS INCLUDED

- RPE/2200 : external stitch adjuster
- EPF/2200 : pneumatic fringe ejector, requires airpressure 4-6 bar

OPTIONS

- CP/2200 : pneumatic pressure foot lifter

REMARKS

- Right and left version available
- 2200C : chain stitch at the back, cut fringes
- 2200NC : cut or non cut fringes
- 3200 : high speed cut fringes at 1200 stitches a minute

SPECIFICATIONS

SPEED

800 fringes pro minute

DENSITY OF FRINGES

15 to 35 fringes pro 10 cm

LENGTH OF FRINGES

Adjustable from 4 to 12 cm

4-8 cm : short fringes (Ref : 2200fc)

6-10 cm : normal fringes

8-12 cm : long fringes (Ref : 2200fl)



SPEED	STITCH WIDTH	THICKNESS	FABRIC FEED	NEEDLES
				
800 _{spm}	10 _{mm}	10 _{mm}	Bottom	1