

TITAN 4500AHC

High speed overedging for car, plane and boat carpets.
Allows easy sewing of inner turns.

APPLICATIONS

This model allows to sew external or internal curves even of a small diameter. The machine is always fitted with a pneumatic footlift and tension opener to make it easier to manipulate the carpet while sewing.



Model DK2500AHC/3 : 3 threads



Standard : 2 threads

ALWAYS INCLUDED

- CP/4500-DAC : pneumatic footlift

OPTIONS

- RPE/4500 : external stitch density
- DCD/4500 : cutting device
- SET 30566 : tape guide
- MEM/2500 : electronic motor
- NCV/2500 : needle cooler
- FK/4500 : oil filter + cooling

REMARKS

- 4500AHC/3 : 3-thread overedging machine available
- 4510AHC : high speed version for thicker carpets available

SPECIFICATIONS

SPEED

3200 stitches pro minute
(high speed serger)

STITCH WIDTH

10 to 12 mm

DENSITY OF STITCHES

1 to 10 stitches/cm

THREADS

Most types of threads

Carburated feeddog included

SPEED	STITCH WIDTH	THICKNESS	FABRIC FEED	NEEDLES
				
3200 _{spm}	10 _{mm}	12 _{mm}	Bottom	1

